

A-57116-5-1/8

HAFNER

(HU) Dugaszolható könyök csatlakozó - fém kivitel




Technical data

Kivitel	menetes
Material	Nickel-plated brass
Port size / Connection	G 1/8"
Medium	Compressed air, vacuum, water, steam
Material seals	NBR
Temperature range	-20°C...+80°C
Operating pressure	-0,9...20 bar
Material retaining ring	Nickel-plated brass
Material support ring	Technopolymer
Pressure range	-0,9...20 bar
Port size Push-in connection	Ø5
Port size	Ø5
Material body	Nickel-plated brass
Material release ring	Technopolymer
Rögzítő karom anyaga	Stainless steel

A-57116-5-1/8

HAFNER

(HU) Dugaszolható könyök csatlakozó - fém kivitel



Type number	Tube size	Port size A	B	L1	L2	CH1	CH2	D
A-57116-4-M5	4	M 5	3,5	18	17,5	9	8	10
A-57116-4-1/8	4	G 1/8"	5,5	18	18	9	13	10
A-57116-4-1/4	4	G 1/4"	7	18	18	9	16	10
A-57116-5-M5	5	M 5	3,5	20	20	11	11	12,5
A-57116-5-1/8	5	G 1/8"	5,5	20	20	11	13	12,5
A-57116-6-M5	6	M 5	3,5	21	20	11	11	12,5
A-57116-6-1/8	6	G 1/8"	5,5	21	20	11	13	12,5
A-57116-6-1/4	6	G 1/4"	7	21	21,5	11	16	12,5
A-57116-8-1/8	8	G 1/8"	5,5	22,5	21	12	13	14,5
A-57116-8-1/4	8	G 1/4"	7	22,5	21,5	12	16	14,5
A-57116-8-3/8	8	G 3/8"	8	22,5	23,5	12	20	14,5
A-57116-8-1/2	8	G 1/2"	9,5	22,5	25	12	25	14,5
A-57116-10-1/4	10	G 1/4"	7	26,5	25,5	14	16	17,5
A-57116-10-3/8	10	G 3/8"	8	26,5	25	14	20	17,5
A-57116-10-1/2	10	G 1/2"	9,5	26,5	26,5	14	25	17,5
A-57116-12-1/4	12	G 1/4"	8	31,5	27,5	16	20	21,5
A-57116-12-3/8	12	G 3/8"	8	31,5	27	16	20	21,5
A-57116-12-1/2	12	G 1/2"	9,5	31,5	28,5	16	25	21,5
A-57116-14-3/8	14	G 3/8"	8	31,5	27,5	16	20	21,5
A-57116-14-1/2	14	G 1/2"	9,5	31,5	29	16	25	21,5
A-57116-6-M12x1	6	M 12 x 1	7,5	20	22	11	16	12,5
A-57116-6-M12x1,25	6	M 12 x 1,25	7,5	20	22	11	16	12,5
A-57116-6-M12x1,5	6	M 12 x 1,5	7,5	20	22	11	16	12,5
A-57116-8-M12x1,5	8	M 12 x 1,5	7,5	22,5	22	12	16	14,5